

Deform-Nut®

SERIE TTN

S E R I E S

THREADED TUBULAR RIVET NUTS WITH LOW PROFILE HEAD

APPLICATION

For head of tubes and cylindrical sections.

ASSEMBLY

By specific manual and pneumatic tools.



CODE	Hole Ø	Total length	Metrical thread	Shaft Ø	Head Ø	Head thicknesses
	(d5) *	(l)	(d1)	(d)	(d3)	(l1) ~
TTN M 6/9,5/8	9,5 ÷ 10,5	13,2	M 6	9,5	10	0,6
TTN M 6/11/8	11,0 ÷ 11,8	15,7	M 6	11	11,7	0,6
TTN M 6/11,5/8	11,5 ÷ 12,5	15,7	M 6	11,5	12	0,6
TTN M 6/12,5/8	12,5 ÷ 13,5	15,7	M 6	12,5	13	0,6
TTN M 6/13,5/8	13,5 ÷ 14,7	15,7	M 6	13,5	14	0,7
TTN M 6/14,8/8	14,8 ÷ 16,2	18,5	M 6	14,8	15,8	0,7
TTN M 6/16,8/8	16,8 ÷ 18,2	21,6	M 6	16,8	17,4	0,7
TTN M 6/18,3/8	18,3 ÷ 19,9	21,6	M 6	18,3	19	0,7

* For a proper use of the product, it is recommended to make some tests to verify the optimal fittings conditions.

MATERIAL

Steel nr. 1.0718

SURFACE TREATMENT

White zinc plating

THREAD TOLERANCE

Metrical tolerance ISO 6H

EXAMPLE OF CODE DESIGNATION

Threaded tubular rivet nuts with low profile head, internal tube diameter 13,0 mm, M 6 thread, steel: **TTN M 6/12,5/8**

Juno Industries BVBA - Stoktevijver 22 - 9930 Zomergem/België/Belgique
Tel/tél: (0)9/395.95.90 - Fax: (0)9/395.95.91 - co@junoindustries.eu

Non binding dimensions, expressed in mm.

