

Deform-Nut®

SERIE ETC/K

S E R I E S

THREADED TUBULAR RIVET NUT WITH ROUND HEAD
AND SEMI-HEXAGONAL SHANK IN STAINLESS STEEL 316



APPLICATION
On boxed and tubular sections, metal sheets, other materials.
ASSEMBLY
By specific manual and pneumatic tools.

CODE	Grip range	Total length	Metrical thread	Shaft Ø	Head Ø	Head thicknesses	Hexagonal hole
	(s)	(l)	(d1)	(ch)	(d3)	(l1)	(d5) $+0,15$ 0
ETC M 4/K	0,5 ÷ 2,0	12,0	M 4	6,0	9,0	1,0	6,0
ETC M 5/K	0,5 ÷ 3,0	12,5	M 5	7,0	10,0	1,0	7,0
ETC M 6/K	0,5 ÷ 3,0	16,0	M 6	9,0	12,0	1,5	9,0
ETC M 8/K	0,5 ÷ 3,0	17,5	M 8	11,0	15,0	1,5	11,0

MATERIAL

Stainless steel AISI 316 (on demand)

SURFACE TREATMENT

Natural state

EXAMPLE OF CODE DESIGNATION

Threaded tubular rivet nut with round head and semi-hexagonal body, grip thicknesses 2,0mm, M 6 thread, AISI 316 stainless steel: **ETC M 6/K**

Juno Industries BVBA - Stoktevijver 22 - 9930 Zomergem/België/Belgique
Tel/tél: (0)9/395.95.90 - Fax: (0)9/395.95.91 - co@junindustries.eu

Non binding dimensions, expressed in mm.

